



## 3410 / 3410 P

**3410** - Compactor with vibratory smooth roller drum

**3410 P** - Compactor with vibratory padfoot drum



- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Optimum ease of maintenance, long service intervals
- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ Hydrostatic steering
- ▶ Clear information display



Authorised Dealer



**DAI LIENG MACHINERY SDN BHD (130903-K)**

Lot 2541, Jalan Manettia, Jalan Plasau, Lorong 8,  
Pujut-Lutung Road, P.O.Box 1337  
98008 Miri, Sarawak, Malaysia.  
Tel: +60 85 655 855 Fax: +60 85 655 618  
Email : headoffice@dailieng.com.my  
Website : www.dailieng.com.my

# 3410 / 3410 P

3410 - Compactor with vibratory smooth roller drum  
3410 P - Compactor with vibratory padfoot drum



	3410	3410 P
<b>Weights</b>		
Operating weight with ROPS	kg 10410	10600
Operating weight with cab	kg 10700	10890
Operating weight, max.	kg 12230	12420
Axle load, front/rear	kg 5785/4915	5975/4915
Load per tyre, rear	kg 2457,5	2457,5
Static linear load, front	kg/cm 27,0	27,9
French classific., data/class	38,2/VM2	38,0/VM2
<b>Machine dimensions</b>		
Max. working width	mm 2140	2140
Lateral overhang, left/right	mm 55/55	55/55
Ground clearance, left/right	mm 447/447	497/497
Ground clearance, centre	mm 359	410
Turning radius, inside	mm 4670	4670
Drum type, front	smooth	Padfoot
Drum thickness, front	mm 25	15
Padfeet, number		140
Height of the padfeet	mm 100	100
Front area of padfeet	cm <sup>2</sup>	152
Size of tyres, rear	AW 23.1-26 12 PR	TR 23.1-26 12 PR
<b>Diesel engine</b>		
Manufacturer	DEUTZ	DEUTZ
Version	BF4M 2012C	BF4M 2012C
Number of cylinders	4	4
Power rat. ISO 14396, kW/PS/rpm	98,0/133,3/2300	98,0/133,3/2300
Power rating SAE J1349, kW/HP/rpm	98,0/131,3/2300	98,0/131,3/2300
Emissions standard EU/USA	II / Tier 2	II / Tier 2
Fuel tank, capacity	L 290	290
<b>Drive</b>		
Hydrostatic drive, front/rear		Wheel motor/axle
Speed, working gear	km/h 0-5,6/0-7,3/0-7,8	0-5,9/0-7,6/0-8,2
Speed, transportation gear	km/h 0-11,5	0-12,0
Climbing ability, vibration on/off	% 48/53	48/53
<b>Vibration</b>		
Vibration frequency, front, I/II	Hz 30/40	30/40
Amplitude, front, I/II	mm 1,90/0,80	1,90/0,80
Centrifugal force, front, I/II	kN 246/144	246/144
<b>Steering</b>		
Steering, type	Articulated steering	Articulated steering
Steering, actuation	hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	33	33
Oscillation angle +/-	10	10

Authorised Dealer



**DAI LIENG MACHINERY SDN BHD (130903-K)**

Lot 2541, Jalan Manettia, Jalan Plasau, Lorong 8,  
Pujut-Lutong Road, P.O.Box 1337  
98008 Miri, Sarawak, Malaysia.  
Tel: +60 85 655 855 Fax: +60 85 655 618  
Email : headoffice@dailieng.com.my  
Website : www.dailieng.com.my

<b>Total length</b>	L	5695	5695
<b>Width</b>	B	2250	2250
<b>Total height</b>	H	2944	2994
<b>Wheel base</b>	A	3007	3007
<b>Drum width</b>	X	2140	2140
<b>Drum diameter</b>	D	1504	1684
<b>Width over tyres</b>	Y	2106	2132
<b>Diameter of tyres</b>	R	1520	1606
<b>Height loading, min.</b>	HI	2264	2314

