

HOWARD AGRICULTURAL ATTACHMENT



Over the years, HOWARD Malaysia has diversified its product range to cater also for palm oil plantations, turf-care and road maintenance, besides its traditional soil preparation for paddy fields.

Soil Preparation



ROTAVATOR | B-16



B-16, compact and lightweight, suitable on small farms, in paddy fields and in cash crop agriculture for primary & secondary tillage. Compact & lightweight, with low horsepower requirement.

ROTAVATOR | B-18



B-18, suitable for medium size farms. PTO with A6 size & shear bolt torque limiter protection will increase capability to work at semi-hard ground. Medium-duty side gear drives for smooth reliable performance.

ROTAVATOR | B-26



B-26 is designed for general soil separation in wet or dry land conditions. With multi-speed gear-setting, B-26 provides choices of tillage to suit crop, soil & climate. Powerful transmission to protect machine & tractor against shock-loads.

ROTAVATOR | B-36



B-36 is ideal for 'built-on' combinations, Ripper, Furrower or Crumble Roller. Side drive through heavy-duty Roller Chain - 17 ton breaking load with externally adjustable tensioning skids.







POST HOLE DIGGER | PHD 45



- It digs a smooth hole to 90cm depth.
- Comes with optional auger sizes; 9", 12", 18", 20", 24"
- Takes less than a minute to dig a suitable planting hole, and with pre-set markers and driving/positioning time.
- A skilled operator can complete 30-40 holes/hours.

FURROWER / RIDGER



- Suitable for furrowing and preparing dry land seed beds for vegetables or nurseries.
- Able to make 1,2 or 3 furrows depending on choice.
- Can be used individually on mounted onto Howard Light Duty Rotavator model B16 of Howard Heavy Duty Rotavator model B36.

DICS PLOUGH



- A versatile plough suitable for uneven ground that has hidden obstacles such as rocks and roots.
- The Disc Plough is used for primary cultivation which is the first stage in seed bed preparation.
- Disc Ploughs are available in different arrangement, they all come with standard three-point CAT II linkage and 26-inch discs, with its robust design.







Grass Control

ROTALASHER HS/HSR 14/90 | 14/120



Hitched to any mini-tractor, HS 14 will provide economical & excellent grass maintenance for sports field, road sides and parks. Tractor PTO drive (540 rpm) protected by shear bolt torque limiter. Fast-rotating sharp swing-back blades. Stepless height adjustment.

ROTALASHER HS/HSR 34/150 | 34/180



A heavy-duty performer, HS-34 is equally suitable for road-side plantations maintenance for undergrowth clearing. Fitted with clutch protection, this machine is capable slashing bushes & small trees. Heavy-duty blades, mounted in hardened journal. Universal PTO drive shaft with clutch.

ROTALASHER HS/HSR 24/120 | 24/150



HS-24 is designed for the medium duty tractor range. Cutting of grass with cylinder/bedknife (reel mower) leaves a neater finish & is recommended on fine turf areas such as golf course greens. A6 Universal Driveshaft with shear bolt protection. Stepless height adjustment.

ROTALASHER HS/HSR 24/120 | 24/150



HS-44 is widely used for stubble shaving, ratooning & mulching of fibrous crop such as sugarcane & pineapple. Chain slashing Heads & Dics Stubble Shaver available as optional. Extra Heavy Duty machine that will continuously stand up to demanding tasks. Drive train protected by metal wearing disc and 4 bronze friction dics.



HOWARD AGRICULTURAL ATTACHMENT



Grass Control

ROADSWEEPER | HTS 180



A PTO driven brush for rear tractor-mounting that can be angled left & right. Includes dust flap & parking leg as standard features. Height is easily adjusted via two swivel castor wheels. Easy changeable polypropylene circular bristle disc and the mixture of alternating wire/PP bristles are available as optional.

MINING BUCKET | HMB 210



Functional design with rigid material and workmanship. HMB 210 is a useful contractor's implement for road building, levelling, on construction sites or for quarry work. With springloaded tip-lock.

GRADER | HMG 270



A heavy-duty rear mounted grader, equipped with multiple features such as vertical tilt for ditching, multiset locking 15°-30°-45°, and offset positioning on both sides of the tractor. HMG is useful for tasks as road maintenance, slurry scraping, landscaping & ditching. HMG can swivel 360°, and be set for reverse levelling.