


ROADSWEEPER


HTS 180



| Model ROADSWEEPER | HTS180 |
|-----------------------------|--|
| Dimension in mm (L x W x H) | 2074 x 1328 x 1156 |
| Working Width, cm | 180 |
| For Tractor, Hp | 35-90 |
| 3-Point Linkage, CAT | I/II |
| Universal Driveshaft | A4 c/w Shearbolt Limiter Torque |
| Type Of Brush | Circular Bristle Polypropylene & Wire (Optional) |
| No of Brush | 41 |
| Side Transmission Drive | Chain & Sprockets |
| Brush Speed at 540 rpm | 282 |
| Angle Adjustment Position | 3 |
| Height Adjustment | Rear Swivel Tyre |
| Weight (kg) | 370 |









Right Angle

Left Angle

HOWARD's Roadsweeper HTS 180 is a PTO driven brush for rear tractor-mounting. It can be angled left and right, and comes with dust flap and parking leg as standard features.

Designed for easy service and maintenance with spareparts readily available.

Power is transmitted via universal driveshaft through an oil bath gearbox, transmission shaft and chain and sprocket sidedrive.

Height is easily adjusted via two swivel castor wheels.

Easy changeable polypropylene circular bristle discs (41). Mixture of alternating Wire/PP bristles available as optional.

