

ROTASLASHER

HS/HSR
24/120
24/150



Model	HS/HSR	HS24/120	HSR24/120	HS24/150	HSR24/150
Dimension, mm (L x W x H)		1560 x 1430 x 895	1845 x 1430 x 910	1780 x 1700 x 895	2070 x 1700 x 910
Working Width, cm		120		150	
For Tractor, Hp		35-45hp		45-60hp	
3-Point Linkage, CAT		I/II			
Universal Driveshaft		A6 c/w Shearbolts torque limiter			
Blade Speed at 540 rpm		1042			
Cutting Heights, cm		1 - 10			
No of Blades		2			
Size of Blades, mm		90 x 8			
With Front and Rear Roller		NO	YES	NO	YES
Type of Blade		Cranked and Swing			
Weight (kg)		190	220	250	280

Blade



PTO Drive Shaft



Swing-Back Blade



Changeable Roller Kit



The most versatile slasher for general grass and weed control, HS-24 is designed for the medium duty tractor range. Suitable for grass cutting on a continuous basis, thus providing a very short pay-back time for professional contracting jobs. Blades designed to lift grass prior to cutting. Stepless height adjustment. A6 Universal Driveshaft with shear bolt protection. Cutting of grass with a cylinder/bedknife (reel mower) leaves a neater finish and is recommended on fine turf areas such as golf course greens. But if speed and economic consideration prevail, rotaslashing is superior. Moreover, slashed clippings are thoroughly smashed: decompose faster-adding nutrients to the soil, and should, as a general rule, therefore not be removed.

