

ROTASLASHER

HS/HSR
44/150
44/180



Model	HS/HSR	HS44/150	HSR44/150	HS44/180	HSR44/180
Dimension, mm (L x W x H)		2012 x 1669 x 1081	2254 x 1669 x 1081	2117 x 1975 x 1081	2365 x 1975 x 1081
Working Width, cm		150		180	
For Tractor, Hp		Above 70hp			
3-Point Linkage, CAT		I/II			
Universal Driveshaft		A7 PTO Drive Shaft Assembled with Sintered Metal Disc Slip Clutch Assy			
Blade Speed at 540 rpm		1026			
Cutting Heights, cm		1 - 10			
No of Blades		2			
Size of Blades, mm		75 x12			
With Front and Rear Roller		NO	YES	NO	YES
Type of Blade		Cranked and Swing			
Weight (kg)		340	370	490	520

Blade



Clutch



PTO Drive Shaft



As a general rule, this machine will deal effectively with any jungle undergrowth which a tractor can ride over. HS 44 is also widely used for stubble shaving, ratooning and mulching of fibrous crops such as sugarcane and pineapple.

Chain slashing Heads and Disc Stubble Shaver available as optional.

Extra Heavy Duty machine that will continuously and uncompromisingly stand up to the most demanding land clearing tasks. Drive train protected by metal wearing disc and four bronze friction discs.

