


# ROTAVATOR | B-26



Model	B26	155	180	205
<b>Dimension, mm (L x W x H)</b>		1805 x 1025 x 1060	2060 x 1025 x 1060	2315 x 1025 x 1060
<b>Working Width, cm</b>		155	180	205
<b>For Tractor, Hp</b>		40-55hp	45-70hp	65-80Hp
<b>3-Point Linkage, CAT</b>		I/II		
<b>Universal Driveshaft</b>		A6 c/w FF2 Slip Clutch		
<b>Gearbox</b>		Multi Speed		
<b>No of Flanges</b>		7	8	9
<b>No of Blades</b>		36	42	48
<b>Size of Blades, mm</b>		75 x 6		
<b>Rotor Speed at 540 rpm</b>		158 / 176 / 221 / 247		
<b>Side Transmission Drive</b>		Rollerchain & Sprocket		
<b>Max Working Depth, cm</b>		16		
<b>Type of Blade</b>		C or L (Optional)		
<b>Weight (kg)</b>		350	390	440

L / C Blade



Face Seal



Gearbox



PTO Drive Shaft



Model B-26 requires min. 45 hp and is designed for general soil preparation in wet or dry-land conditions. With multispeed gear-settings, B-26 provides a wide choice of tillage - to suit crop, soil and climate. Powerful transmission with inbuilt safety features to protect machine and tractor against shock-loads.

A popular workhorse for contractors, its many features are neatly incorporated in a simple design - userfriendly and easy to maintain. All models come with metal to metal face seals to prevent water from contaminating transmission oil when working in wet conditions

