


ROTAVATOR | B-36



Model	B36	155	180	205	230	255
Dimension, mm (L x W x H)	1805 x 1025 x 1100	2060 x 1025 x 1100	2315 x 1025 x 1100	2570 x 1025 x 1100	2825 x 1025 x 1100	
Working Width, cm	155	180	205	230	255	
For Tractor, Hp	55-60hp	60-75hp	70-90hp	90-110hp	90-110hp	
3-Point Linkage, CAT						I/II
Universal Driveshaft						A8 c/w FF4 Slip Clutch
Gearbox						Multi Speed
No of Flanges	7	8	9	10	11	
No of Blades	36	42	48	54	60	
Size of Blades, mm						80 x 7
Rotor Speed at 540 rpm						166 / 203 / 144 / 235
Side Transmission Drive						Rollerchain & Sprocket
Max Working Depth, cm						18
Type of Blade						L or C (Optional)
Weight (kg)	470	510	550	590	630	



Multi Speed Gear

This extra-heavy-duty rotavator performs excellently in demanding conditions and is ideal for “built-on” combinations - such as Ripper, Furrower or Crumble Roller.

Side drive through heavy-duty Roller Chain - 17 ton breaking load - with externally adjustable tensioning skid. Rotor drive is supported by large ball bearings and face seals.

Protection of tractor and transmission against shock-loads ensured by heavy - duty safety clutch.

Cultivating depth is adjustable by raising or lowering the side skids.

Depth control wheels available as optional.

Selectatilh pick- off gears allow four alternative rotor speeds (540 PTO)

