



PX9020

90 HP



SPECIFICATIONS

Model		PX9020
Engine		
Manufacturer		Perkins
Model		1104C-44TTG
Engine Gross Power	HP(kw)	89.2(66.5)
Rated revolution	rpm	2200
Type		4Cyl., In-line Vertical, Water-cooled
Total displacement	cc(cu in.)	4399(269)
Turbo Charge		0
Capacity		
Fuel tank	ℓ(us gal)	120 (31.7)
Support of front axle	ℓ(us gal)	LSD 10(2.64) Front axle case: R/L 0.9 (0.24)
PTO		
Rated PTO Power/rpm	HP(kw)/rpm	72.7(54.2)/572
PTO Efficiency	%	87
Rear PTO Type		Independent
Rear PTO rpm	rpm	540/1000
Ground PTO		Std
Hydraulic		
3 Point Lift Control Type		Position, Draft, Mixed Control
Total hydraulic flow	lpm(cc/rev)	79.2(36)
3-point hitch type		Category II
Lift Capacity@lift point	kg.f(lbs)	2400(5291)
Drawbar type		Drawbar
Towing Power	ps(KW)	80(59)
No.of standard remote valves (Front/Rear)		(4 / 4)
Drive Train		
Transmission		Synchro mesh(Main) / Constant mesh(range)
No. of speeds		16×16
Shuttle Type		Synchromesh
Steering		Hydrostatic Power Steering
Mechanical differential lock		Rear Standard
Traveling Speeds		
Forward	km/h(mph)	0.75~37.47(0.47~23.28)
Reverse	km/h(mph)	0.73~36.47(0.45~22.66)
Dimensions		
Overall length (w/o front weight and w/3pt hitch)	mm(in.)	4120(162.2)
Overall width (minimum tread)	mm(in.)	2000(78.7)
Tread width - Front	mm(in.)	1643(60.7)
Tread width - Rear	mm(in.)	1532(60.3)
Overall height (ROPS)	mm(in.)	2900(114.2)
Wheel base	mm(in.)	2305(90.7)
Ground(Crop) clearance	mm(in.)	445(17.5)
Turning radius(w/brake)	mm(in.)	4160(163.8)
Weight with ROPS	kg.f(lbs)	3500(7716.2)
TIRE SIZE		
AG. Tire Front		12.4-24, 8PR
AG. Tire Rear		18.4-30, 8PR

* NOTE : Specifications and design are subject to change without notice.



ISO 9001
NO.954596



ISO 14001
NO.771475



OHSAS 18001
NO:K033008

STANDARD EQUIPMENT

- Creep gear
- 4WD
- Auto 4WD
- Rear PTO
- Rear Weight
- Rear Remote Hydraulic Valve
- Joystick valve
- AUTO PTO
- Draft Control
- ROPS
- Rear View Mirror
- Parking Brake
- Air Cleaner
- Battery
- Horn
- 7 Pin Socket
- Head Lamp
- Working Light
- Signal Lamp
- Backward Lamp
- Seat Armrest
- PTO Cover
- Cup Holder
- Outside Lift Control

OPTIONAL EQUIPMENT

- Support for front weight
- Front Weight
- Additional hyd. Lift cylinder
- Front Fender
- Sun Canopy



DAI LIENG TRADING SDN BHD (223694-K)
 Lot 2541, Jalan Manettia, Piasau Lorong 8,
 Pujut-Lutong Road, P.O. Box 1337,
 98008 Miri, Sarawak, Malaysia
 Tel: 085-655855 (6 lines) Fax: 085-655618
 E-mail : info@dailieng.com.my
 Website: www.dailieng.com.my