



HOOKLIFT

The first MULTILIFT was delivered in 1949. Today there are effective MULTILIFT hooklift for almost every imaginable task. Explore our range and get in touch today to find your ideal match. Our hooklift provide market-leading productivity and reliability to give you the edge over any challenge load handling throws at you.

- Computer aided design and robot welded high tensile steel - lowest weight & highest quality.
- Hydraulic buffer system in outer boom cylinder to improve durability.
- Integrated hydraulic shock absorber system to ensure long lifetime.



Type	XR 5S		
Capacity (kg)	5000		
Gvw of the vehicle (t)	7.5		
Container length (internal) (m)	3.0 - 4.0	3.5 - 4.5	4.0 - 5.0
G-length (mm)	3250	3650	4150
Equipment weight (kg)	650	690	730
Tipping angle (°)	49	49	48
Hook height (mm)	930		
Body level (mm)	160		
Max. operating pressure (mpa)	30		
Recommended oil flow (l/min)	20 - 25		



MULTILIFT

HOOKLIFT



Type		XP14T			
Vehicle type		2 axle			
GVW of the vehicle (t)		19			
Capacity (t)		14			
G-length	41	43	46	51	
System weight (kg) *	1610	1640	1670	1770	
Tipping angle (°)	49	47	50	49	
Max. operating pressure (MPa)		30			
Recommended max. oil flow (l/min)		60			



Type		XP18T	
Vehicle type		3 axle	
GVW of the vehicle (t)		26	
Capacity (t)		18	
G-length		46	51
System weight (kg) *		1780	1880
Tipping angle (°)		50	49
Max. operating pressure (MPa)		30	
Recommended max. oil flow (l/min)		80	