



# JUSTAR J600 Premium

**10W-40**  
 Engine Oil

**API SN/CF**  
 Synthetic Technology  
 BMW Longlife-01  
 VW 50200/50500



## Typical data

| SINOPEC JUSTAR J600 Premium 10W-40 Engine Oil              |        |
|--|--------|
| SAE grade  | 10W-40 |
| Kinematic viscosity, ASTM D 445                            |        |
| cSt@ 100°C   | 14.17  |
| Dynamic viscosity, CCS, ASTM D 5293                        |        |
| cP@ -25°C  | 3,700  |
| Mini-rotary viscometer (MRV), ASTM D 4684                  |        |
| cP@ -30°C  | 18,000 |
| High-temperature, high-shear viscosity (HTHS), ASTM D 4683 |        |
| cP@ 150°C  | 3.80   |
| NOACK volatility, ASTM D 5800                              | 10.4   |
| Sulfated ash, wt%, ASTM D 874                              | 1.1    |
| Total base number, mg KOH/g, ASTM D 2896                   | 10.1   |

These data are given as an indication of typical values and not as exact specifications.

## Product description

SINOPEC JUSTAR J600 Premium 10W-40 Engine Oil is a premium product formulated with fully synthetic base oils and high-quality multifunctional additive technology. It provides excellent oxidation resistance, deposit and wear protection, coupled with low-temperature performance for service in a wide range of modern, high-performance petrol and light duty diesel-powered vehicles.

## Applications

SINOPEC JUSTAR J600 Premium 10W-40 Engine Oil is suitable for use in:

- Cars meet the Porsche, BMW, Benz, Volkswagen, Renault and other technical requirements;
- High-performance passenger cars, racing cars and coaches equipped with multi-valves, variable valve timing, turbochargers and direct-injection engines.
- Engine requiring oils of A3/B4 grade.

## Features and benefits

- Using high-quality base oils, lasting protection and power for EFI engine with or without turbocharger.
- Balanced start up performance in low temperature and lubricating properties in high temperature.
- Excellent anti wear performance, reducing wear effectively to extend engine life.
- Superior oxidation stability and cleaning power to prevent deposits and sludge build-up.



## Industry and OEM specifications

|                            |                                |
|----------------------------|--------------------------------|
| ACEA                       | A3/B4                          |
| API Service Classification | SLand earlier specifications   |
| BMW                        | Longlife-01                    |
| BENZ                       | MB 229.3, MB 229.5             |
| Porsche                    | A40                            |
| Renault                    | RN0700, RN0710                 |
| Volkswagen                 | VW 50200/50500, VW 50101/50500 |